



HP: .33-15
Pole: 2/4/6

Frame: 56C-215T
Volt: 230/460V

RPM: 3600/1800/1200
Body: T



STANDARD FEATURES



- NEMA Premium Efficiency
- IP 56 Rated Protection
- 50/60 Hz Capable
- 1.15 Service Factor
- 9 Lead Dual Voltage
- Double Lip Oil Seals on DE & ODE
- Inverter Rated 15:1 Constant Torque for VFD use
- Multi-mount Removable Feet
- F1, F2, F3 Field Convertible (Shipped F1)
- Class F Insulation System (Class H Stator)
- One-Way Brass Condensation Drains on DE & ODE
- Designed to Class B Temperature Rise
- Drive End Bearing Locks
- VPI Insulated Windings
- EISA Compliant
- 24 Month Warranty
- Fully Potted Conduit Entry

HP	SYNC SPEED	Model Number
1/3	3600	WX3-AL-TF-56C-2-B-D-.33
	1800	WX3-AL-TF-56C-4-B-D-.33
1/2	3600	WX3-AL-TF-56C-2-B-D-.5
	1800	WX3-AL-TF-56C-4-B-D-.5
3/4	3600	WX3-AL-TF-56C-2-B-D-.75
	1800	WX3-AL-TF-56C-4-B-D-.75
1	3600	WX3-AL-TF-56C-2-B-D-1
	1800	WX3-AL-TF-56C-4-B-D-1
	1800	WX3-AL-TF-143T-4-B-D-1
	1200	WX3-AL-TF-145T-6-B-D-1
1.5	3600	WX3-AL-TF-56C-2-B-D-1.5
	1800	WX3-AL-TF-56C-4-B-D-1.5
	3600	WX3-AL-TF-143T-2-B-D-1.5
	1800	WX3-AL-TF-145T-4-B-D-1.5
2	1200	WX3-AL-TF-182T-6-B-D-1.5
	3600	WX3-AL-TF-56C-2-B-D-2

HP	SYNC SPEED	Model Number
2	1800	WX3-AL-TF-56C-4-B-D-2
	3600	WX3-AL-TF-145T-2-B-D-2
	1800	WX3-AL-TF-145T-4-B-D-2
3	1200	WX3-AL-TF-184T-6-B-D-2
	3600	WX3-AL-TF-56C-2-B-D-3
	3600	WX3-AL-TF-182T-2-B-D-3
5	1200	WX3-AL-TF-213T-6-B-D-3
	3600	WX3-AL-TF-184T-2-B-D-5
	1800	WX3-AL-TF-184T-4-B-D-5
7.5	1200	WX3-AL-TF-215T-6-B-D-5
	3600	WX3-AL-TF-213T-2-B-D-7.5
10	1800	WX3-AL-TF-213T-4-B-D-7.5
	3600	WX3-AL-TF-215T-2-B-D-10
15	1800	WX3-AL-TF-215T-4-B-D-10
	3600	WX3-AL-TF-215T-2-B-D-15