# UC-HL4.5 4½" Launcher & Kits



## Features & Benefits

- Capable of cleaning 1/8" through 4-1/2" hose, tube or pipe.
- UC-HL4.5 Launcher comes complete with the UC-4.5LN aluminum locking nozzle.
- UC-HL4.5 Launcher is supplied with a -8 SAE male flare and female swivel with 1/2" hose barb for correct SCFM air flow requirements.
- Capable of passing 50% more SCFM than our other launchers. This is extremely important when doing applications above 3-1/2" and long lengths of hose, tube or pipe.
- Manufactured from precision machined aluminum and fully anodized for harsh environments and heavy use.
- Ideal for job site applications because of its simplistic design, size and portability.
- The UC-HL4.5 is capable of cleaning 1/8" through 3-1/2" when combined with our adapter rings and nozzles using the UC-LR locking ring in place of the UC-4.5LN locking nozzle.

### Air Requirements

- 80 PSI (5.5 Bar) minimum to 110 PSI (7.5 Bar) maximum.
- 1/2" ID air hose to ensure 110 SCFM (3.1 m<sup>3</sup>/min) air flow.
- 5 micron filter and regulator with gauge are strongly suggested!

#### Available Kit (1)

- Kits are customizable based on customer requirements. Call us to discuss your specific needs.
- Information on kit items can be found throughout the Clean Easy section of this catalog.

### UC-HL-1-4.5 Kit



Includes:

- UC-HL4.5 Launcher
- UC-AR2 Adapter Ring
- UC-AR3 Adapter Ring
- UC-LR Aluminum Locking Ring
- UC-H4.5LN Aluminum Locking Nozzle

