

## **UC-EL1.25**

### *Ultra Clean Hand Launcher 1 1/4"*



#### **Description:**

Pneumatic actuated launcher designed for occasional use on applications up to 1 1/4" ID.

#### **Features:**

1/4-Turn locking ring with knurled grip surface; full-flow 1/2" quick-disconnect (not shown); ergonomic design; built-in notch for mounting onto launcher stand.

(Picture of UC-EL1.25 launcher shown with UC-H19 hose nozzle, sold separately)

#### **Specifications:**

Part Number	Color Code	Weight	Weight	Dimensions	Dimensions
		Lbs.	Kg.	(L x W x H) Imperial	(L x W x H) Metric
UC-EL1.25	Teal Handle, Silver Face Plate	1.2	0.544	6 1/4" x 2 1/2" x 7 3/4"	158.75mm X 63.5mm X 196.9mm

#### **Air Requirements:**

80psi (5.5 Bar) minimum to 110psi (7.5 Bar) maximum.

1/2" ID air supply hose to ensure 55 SCFM (1.6m<sup>3</sup>/min) air flow.

5-Micron (5μ) air filter & regulator with gauge are strongly suggested!

#### **Material(s):**

Steel & brass internal construction

Acetyl plastic body



1. Unscrew Locking ring from firing head.

2. Load projectile into nozzle and screw locking ring onto firing head.



3. Connect supplied UC-QRC-C to a ½"ID air hose to launcher and insert nozzle into hose, tube or pipe.



