# SIGHT GAGES - CLOSED CIRCUIT

**Standard Materials:** 

Buna N seals

(21°C)

page RA-A5)

Constructed with a molded, transparent Nylon

212°F (100°C) maximum operating temperature

50 psi (345 kPa) maximum operating pressure at 70°F

• Please refer to Temperature Ratings by Seal Material

for additional operating conditions (Appendix RA-5 on

• Red color alcohol within thermometer bulb

**Temperature and Pressure Ratings:** 

# **GT623 SERIES**

GT623 Series front mount closed circuit low profile sight gages are molded from a clear Nylon providing 180° of viewing. A white insert integral to the sight gage helps draw eye contact to the fluid level quickly.

### **Standard Features:**

- Front mount
- Tough, break resistant, transparent molded Nylon gage body
- 180° of viewing fluid level
- Viewing enhanced by white background integral to molded gage body
- Card thermometer, dual scale 0°F to 220°F and -20°C to 110°C
- Suitable for use with most hydraulic and machine lubricating oils

### NOTE:

• Please refer to Appendix RA-9 on page RA-A9 for installation instructions

## **CAUTION:** • Not recommended for use with alcohol or steam

#### 1.12 [28.4] 67 .85 [21.5] 59 [17.1] [15] .DI D NDUSTRIE 101-----NDUSTRIES MANITONIOC V THITOWOC W USA IJ 1-100-100-5.00 [127] -200 -20 6.12 [155.4] 6.41 [162.7] -20 80-1 1 1 1 1 1 1 1 1 1 80--160 -160 -160 60-60jį. -120 -120 40-20--120 40ij! -80 -80 -80 20-0-١ -40 -40 -40 ΪĮ. -0 -0 -0 20 粡 1/2-13UNC-2A-Ŋ 66 75 [42 2] WITH OPTIONAL GUARD [|9.|]


**NOTE:** All dimensions are inches [mm]

#### **ORDERING OPTIONS CODES:**

#### SEAL MATERIAL

-1- -3- -M-	Buna N seals (standard) Viton® seals (optional) M12 x 1.75 bolts (optional)
-M-	
-G-	Guard (optional)

HOW TO ORDER



Dimensions and specifications are subject to change without notice. Not all items are Made-To-Stock, contact us for availability.

Ph: 920-682-6877 Fx: 920-684-7210



sales@ldi-industries.com www.ldi-industries.com

02/15