


Nickel-Plated Brass DOT Fittings NPTF/Inch Series ND ND6750 Tube Cap

Tube Diameter OD : 5/32", 1/4", 3/8", 1/2", 5/8", 3/4"

Thread Type : 1/8", 1/4", 3/8", 1/2", 3/4" NPTF

PUSH-IN FITTINGS

| DIMENSIONS (in inches) | | | | |
|------------------------|---------|-------|-------|-------|
| Mod. | A OD | C | F | L |
| ND6750 53-00 | 5/32 | 0.520 | 0.346 | 0.591 |
| ND6750 04-00 | 1/4 | 0.606 | 0.472 | 0.610 |



The US Department prohibits the use of air brake tubing assemblies between the frame and axle or between a towed and towing vehicle.

- Meets all requirements for Federal DOT Standard 571.106* 49 CFR Ch. V
- Meets all requirements for SAE J2494-3

- Temperature Range: -58°F to 200°F
- Electrolytic Nickel Plated brass body with a low temperature BUNA-N O-ring
- For use with SAE J844 A & B Nylon tubing
- Compressed air applications

GENERAL DATA

| | |
|---------------------------|---|
| Material | Electrolytic Nickel-plated brass OT58 UNI 5705, Tube-support/insert in glass-reinforced Nylon |
| Collet | Brass OT58, nickel plated |
| O-ring | Low temperature Buna-N (NBR) |
| Threads | 10/32 UNF, 1/8", 1/4", 3/8", 1/2", 3/4" NPTF |
| Temperature Range | -58°F - 200°F |
| Operating pressure | 0 - 275 psi (3/4" tube size operating pressure = 0 - 175 psi) |
| Fluid | Compressed air [for other types of fluid please contact your local Camozzi branch] |
| Tube diameter | 5/32", 1/4", 3/8", 1/2", 5/8", 3/4" OD |