




HOSE REELS

Reels shipped standard sf hose payout position. For ceiling mount add suffix sc.

Inlet — 1/2" FPT Max. Temp. — 200°F





For 3/8" and 1/2" Hose I.D.

Unitract™ Series

LOW PRESSURE reels are ideally suited for plant maintenance or many other industrial functions where hose storage is a problem. Standard hose for air, water and oxygen/acetylene applications. Hose can be dispensed and retracted with greater ease and expedience than coiling by hand. The Unitract™ series fits easily into height restricted areas, and is a lighter duty reel. Not designed for truck mount applications.

FEATURES

- Weighs 10 lbs. less than our standard reels
- Unitized multi-functional hub arbor
- 8 Position guide arm
- Minimal size envelope permits installation where space is a factor
- Simple design incorporates fewer parts
- Single set screw to access latch area and spring case
- Heavy gauge base with no welds

	Model Number	Operating Pressure	Hose I.D.	Hose Length	Shipping Weight
	UTL-300*	1000 PSI	3/8 IN.	—	36#
	UTL-325	300 PSI	3/8 IN.	25 FT.	38#
	UTL-330	300 PSI	3/8 IN.	30 FT.	38#
	UTL-335	300 PSI	3/8 IN.	35 FT.	40#
	UTL-340	300 PSI	3/8 IN.	40 FT.	41#
	UTL-350	300 PSI	3/8 IN.	50 FT.	41#
	UTL-500*	1000 PSI	1/2 IN.	—	36#
	UTL-540	300 PSI	1/2 IN.	40 FT.	43#
	UTL-550	300 PSI	1/2 IN.	50 FT.	47#

* Models without hose.

