

HOSE REELS

3/8" & 1/2" Hose ID – Inlet 1/2" FPT
3/4" & 1" Hose ID – Inlet 1" FPT


Reels available only
in standard rf hose
payout position.

Ceiling mount bracket
available on page 18


Mounting holes 1/2" dia.
for max 3/8"dia. bolt

	3/8 & 1/2	1/2 Dual	3/4 & 1
A	12 1/2	16 1/2	16 1/2
B	6	10	10
C	10	14	14
D	11 5/8	15 5/8	*20

*with swivel installed



Max. Temp. — 200°F



For 3/8", 1/2", 3/4", and 1" Hose I.D.

D Series

Meets requirements for higher volume 3/4 and 1 inch hose applications. Suitable for air, water, oil, diesel fuel and grease where longer lengths of hose are required.

FEATURES

- Safety banded spring in sealed springcase
- Full 1 inch flow path
- Compact design
- Guide rollers allow frictionless retrieval of hose
- Heavy duty spool and frame design

MEDIUM PRESSURE Oils, solvents

MD-300	4000 PSI	3/8 IN.	—	75#
MD-3100	2500 PSI	3/8 IN.	100 FT.	102#
MD-500*	4000 PSI	1/2 IN.	—	75#
MD-500* dual	4000 PSI	1/2 IN.	— (50 E.A. Hose)FT.	75#
MD-575	2500 PSI	1/2 IN.	75 FT.	95#
MD-700*	2000 PSI	3/4 IN.	—	75#
MD-750	1500 PSI	3/4 IN.	50 FT.	100#

* D Series Reels must be shipped by truck only

* Models without hose.

