



Standard "P" Type Coils

FEATURES:

One piece water resistant encapsulated design.

Numerous terminals and voltages.

Coil interchangeability with Delta Series and Super Series valves.



Heavy gauge color coded lead wire.

Reversible coil (can be installed on cartridges in both directions with equal efficiency.)

NOTE:
FOR COIL SELECTION IN EXTREME CONDITIONS, PLEASE LOOK AT OUR "I" COIL LINE OF ENVIRONMENTAL COILS

STANDARD COIL DATA

P-Type coil 1/2" I.D.



ORDERING INFORMATION


P - * * - * *

WHEN ORDERING
FILL IN ALL BOXES

1: BASIC MODEL NO.	2: TERMINATION	3: VOLTAGE
P-Type One Piece Encapsulated Coil	DL - Double Lead DT - Deutsch on Leads DT04-2P DI - Deutsch - Integral DT04-2P ML - Metri-Pack on Leads (12162000) MI - Metri-Pack - Integral (12162000) PL - Packard on Leads (150 Series) WL - Weatherpack on Leads (12010972) SS - Single Spade DS - Double Spade HC - DIN 43650 (Hirschman) - (AC/DC) CL - Conduit Lead - (AC ONLY)	06 -6VDC 12 -12VDC 24 -24VDC 36 -36VDC 48 -48VDC 25 -24VAC 11 -110VAC 13 -125VAC 22 -220VAC 23 -250VAC 44 -440VAC
	19 WATT STD. COIL	

FEB. 2005
REV H

(ALL COILS DC VOLTAGE EXCEPT AS NOTED)
APPROXIMATE COIL ASSEMBLY WEIGHT: .72 lbs./ .32 kg.



WARNING: The specifications/application data shown in our catalogs and data sheets are intended only as a general guide for the product described (herein). Any specific application should not be undertaken without independent study, evaluation, and testing for suitability.

Phone: (815) 397-6628

Fax: (815) 397-2526

E-mail: delta@delta-power.com



Standard "P" Type Coils

Coil Model Numbers:

Termination	PDL	PSL	PDS	PSS	PHC	PCL		
Description	Double Lead	Single Lead	Double Spade	Single Spade	Hirschmann Connector	Double Lead Conduit	Lead Wire Color	AC Voltage Range
Voltage Amp	6VDC 3.5						ORANGE	
Voltage Amp	12VDC 1.6	12VDC 1.6	12VDC 1.6	12VDC 1.6	12VDC 1.6		YELLOW	
Voltage Amp	24VDC .78		24VDC .78	24VDC .78	24VDC .78		BLUE	
Voltage Amp	36VDC .57				36VDC .57		GREEN	
Voltage Amp	48VDC .40		48VDC .40				BROWN	
Voltage Amp			24VAC .92		24VAC .92	24VAC .92	BLUE/ BLACK	
Voltage Amp					110VAC * .19	110VAC * .19	RED/ WHITE	* 100VAC 115VAC
Voltage Amp					125VAC * .17	125VAC * .17	RED	* 115VAC 130VAC
Voltage Amp					220VAC * .10	220VAC * .10	BLACK/ WHITE	* 200VAC 230VAC
Voltage Amp					250VAC * .08	250VAC * .08	VIOLET/ WHITE	* 225VAC 260VAC
Voltage Amp					440VAC * .05	440VAC * .05	VIOLET	* 400VAC 460VAC

Specifications:

Wattage: 19 watts nominal.

Duty Rating: Continuous duty $\pm 10\%$ rated voltage at 120°F (49°C) ambient.

Minimum Current for Actuation: 80% of rated current at room temperature.

Magnet Wire Class: N for all voltages.

Temperature Range: -40°F (-40°C) to 392°F (200°C)

Lead Wires: 18 gauge, 24" long, 600 volt rating, with strain relief.

Encapsulating Material: Glass filled polyester, resistant to moisture, caustic solutions, fungus and vibrations. Temperature range is -40° (-40°C) to 392°F (200°C).

Color Identification: Black

Note: Delta Power A.C. Coils incorporate integrally molded full wave rectifiers which are rated for reverse voltage peaks of 1000 volts maximum.

A.C. Coils are rated 50/60 HZ.

* Optimum operating voltage noted.

Conduit connectors on A.C. coils have a maximum torque spec of 5 Ft. Lbs.

Arc Suppression Diode Available

WARNING: The specifications/application data shown in our catalogs and data sheets are intended only as a general guide for the product described (herein). Any specific application should not be undertaken without independent study, evaluation, and testing for suitability.

Phone: (815) 397-6628

Fax: (815) 397-2526

E-mail: delta@delta-power.com