

Lowboy Power Unit - Extra High Flow

9503510

• Pressure and Tank Unit • Designed for Use on a Lowboy Trailer or Detached Trailer • Takes the Place of a Hydraulic Wet Kit on a Semi • Electric Start, Battery Included • Painted Black • (6) 5/8" Mounting Holes (Reference Drawing Below for Dimensions) • Engine includes low oil shutdown system • Heavy Duty Frame • Suction Filter: 100 Mesh Suction Filter with 3 PSI Bypass • Gauge: Liquid Filled S.S. Case 0-5000 • Tank: 30 Gallon Nominal, 28.5 Gallon Usable, Fully Baffled, 12 Gauge Steel • 5" Level Sight/ Temperature Gauge Standard • Relief Valve Adjustable from 100-3000 PSI • Relief Valve: Preset to Power Units' Maximum Pressure Capability (3000 PSI) • Pumps: High Performance Pressure Balanced Aluminum Body Gear Pump • Tank Drain Plug: #8 O-ring • Fully Tested Before Shipment, Engine Oil Onboard • Anti-Wear ISO 46 Hydraulic Oil Recommended, ATF Satisfactory • Replacement Components Available From Stock

Specifications

- 24 HP Honda Engine, Electric Start, Fuel Injected
- 30 Gallon Hydraulic Tank (28.5 Gallon Usable)
- 3 Gallon Marine Grade Fuel Tank
- High Efficiency Pressure-Balanced Aluminum Gear Pump
- Provides 10.5 GPM at 3000 PSI
- #12 SAE O-Ring Ports (Pressure & Tank)
- #8 SAE O-Ring Drain Port On Bottom of Tank
- Relief Valve, Adjustable From 100-3000 PSI
- 0-5000 PSI Liquid Filled Pressure Gauge
- Filler Breather, Pressurized With 5 PSI Relief
- Suction Filter With 3 PSI Bypass
- 10 Micron Return Filter
- (6) 5/8" Diameter Mounting Holes for 1/2" Bolts
- Painted Black
- Engine Oil Onboard
- Engine Oil Drain Hose (Capped)
- Fully Tested Before Shipment
- 40.19" x 25.50" x 27.50" (L x W x H)
- 390 Lbs Dry Weight



Stock Number	HP	GPM	PSI	Pressure Gauge	Tank Capacity	A & B Ports	Dimensions L x W x H	Ship Wt.
9503510	24	10.5	3000	0-5000 PSI	30 Gallons	#12 SAE O-Ring	40.19" x 25.50" x 27.50"	515

