

PHONE: (308) 382-0262 FAX: (308) 382-0253

HYDRAULICSTORE.COM

Dump Trailer Power Unit


This dump trailer gas engine powered hydraulic power unit is designed for use on a dump trailer. It takes the place of what is normally a 12 VDC power unit. This professional grade power unit is fully tested before shipment. Simply fill the hydraulic tank, the gas tank, and the engine oil and you're off and running!


Specifications

- 4.6 HP Honda Gas Engine, Recoil Start (Pull Start)
- High Efficiency Pressure-Balanced Aluminum Gear Pump
- Spring To Center Directional Control Valve
- Adjustable Pressure Relief Valve (Preset at 3200 PSI)
- 2.25 Gallon Usable Tank, 12 Gauge Steel, Powder Coated Black
- 0-5000 PSI Stainless Steel Liquid Filled Pressure Gauge
- 3/8" NPTF Filler/Breather
- 100 Mesh Suction Strainer
- Use 5/16" Bolts on Gas Engine For Mounting
- Unit Fully Tested Before Shipment, Engine Oil Shipped with Unit
- Recommend Using Anti-Wear ISO 46 Hydraulic Oil or ATF
- Replacement Components Available from Stock
- Unit Weighs 56 lbs. Dry




| Stock Number | HP | GPM | PSI | Pressure Gauge | Tank Capacity | A & B Ports | Dimensions L x W x H | Ship Wt. |
|--------------|-----|-----|------|----------------|---------------|---------------|-------------------------|----------|
| 9504648 | 4.6 | 2 | 3200 | 0-5000 PSI | 2.25 Gallons | #6 SAE O-Ring | 23.75" x 14.65" x 15.5" | 56 |





μŋ



Dual Valve Add-On Kit

14.65


9504662

Do more with your dump trailer gas engine power unit! This kit allows the user to turn a single valve dump trailer power unit into a dual valve dump trailer power unit. Typically, this second cylinder circuit valve is used for a hydraulic jack on the trailer tongue.

| Stock Number | A & B Ports | Dimensions L x W x H | Ship Wt. |
|--------------|---------------|-------------------------|----------|
| 9504662 | #6 SAE O-Ring | 23.75" x 14.65" x 17.5" | 7 |



 \bigcirc



9504648