

## S E R I E S

## **Metric / DIN**

## Flexdraulic 24°

## Metric / DIN Heavy Male Rigid

(24° Cone Seat)

Part #	Hose I.D.		Metric Thread (T)	Required Tube O.D.	Cutoff (C)	Wrench	
	Inch	Size		mm	Inch	1 (Inch) 🐬	1 (mm)
A04-06F	1/4"	-04	M14 X 1.5	S6	0.96"	9/16"	14
A04-08F	1/4″	-04	M16 X 1.5	S8	1.02″	11/16"	17
A04-10F	1/4"	-04	M18 X 1.5	S10	1.02″	3/4"	19
A06-10F	3/8″	-06	M18 X 1.5	S10	1.02″	3/4"	19
A06-12F	3/8″	-06	M20 X 1.5	S12	1.02″	7/8"	22
A06-14F	3/8"	-06	M22 X 1.5	S14	1.10″	7/8″	22
A06-16F	3/8″	-06	M24 X 1.5	S16	1.10″	<sup>15</sup> / <sub>16</sub> "	24
A08-16F	1/2″	-08	M24 X 1.5	S16	1.12″	<sup>15</sup> /16"	24
A10-20F	5/8″	-10	M30 X 2	S20	1.30″	1³⁄16″	30
A12-20F	3/4″	-12	M30 X 2	S20	1.32″	1³⁄16″	30
A12-25F	3/4"	-12	M36 X 2	S25	1.44"	17⁄16″	36
A16-25F	1″	-16	M36 X 2	S25	1.48"	17⁄16″	36
A16-30F	1″	-16	M42 X 2	S30	1.59"	1 13/16"	46